



Sican Safety Films



Film Type	Product Code	CR	Color	MIL	VLT	IR Reject	UV cut	Solar Energy Rejection	Solar Heat Gain Coefficient
Clear Safety	SRC-50		Transparent	2	85%±3%	12%	99%	24%	0.75
	SRC-100		Transparent	4	85%±3%	12%	99%	23%	0.76
	SRC-175		Transparent	7	82%±3%	14%	99%	23%	0.76
	SRC-275		Transparent	11	84%±3%	13%	99%	23%	0.73
Colored Safety	SRC-100-I05		Super Dark Black	4	5%±1%	14%	99%	54%	0.40
	SRC-100-I20		Dark Black	4	20%±1.5%	12%	99%	59%	0.50
	SRC-100-I30		Black	4	34%±3%	11%	99%	64%	0.61
	SRC-100-05V		Super Dark Silver	4	5%±1%	95%	99%	3%	0.10
	SRC-100-CH20		Black	4	20%±1.5%	15%	99%	42%	0.56
	SRC-100-CH35		Light Black	4	35%±3%	15%	99%	28%	0.61
	SRC-100-CH50		L. L. Black	4	50%±3%	15%	99%	24%	0.62
	SRC-100-GN		Light Green	4	70%±5%	13%	99%	24%	0.75
	SRC-100-BL		Light Blue	4	70%±5%	14%	99%	29%	0.74

*Above colors are for reference only, figures are laboratory test results, actual production may vary from batch to batch

HIGHLIGHTS

Thick and hard coating cover, the safety film is one of the kinds for defending vandalism behaviors. In case of break in / smash & grab, the glass will stay in one piece and will not fall off or scattering, which protect whatever behind the window from smashed glass. Not only preventing scattering, but also make the window to last a longer time when delay of force entry is desired, make it more difficult for one

FEATURES

- Films 5MIL and under can be used in automotive
- Colored Safety Films available, 5MIL and up
- Tough coating cover
- Prevent glass from scattering
- Delay force entry in case of break in / smash