



## Sican Ceramic Safety Films



Film Type	Product Code	CR	Color	MIL	VLT	IR Reject	UV cut	Solar Energy Rejection	Solar Heat Gain Coefficient
Ceramic Safety Films	SRC-100-1070	■	Super Dark Black	4	10%±1.5%	70%	99%	77%	0.42
	SRC-100-2070	■	Dark Black	4	20%±1.5%	70%	99%	77%	0.42
	SRC-100-3070	■	Black	4	32%±3%	70%	99%	71%	0.46
	SRC-100-3545	■	Light Black	4	35%±3%	45%	99%	58%	0.41
	SRC-100-3585	■	Light Black	4	35%±3%	85%	99%	75%	0.27
	SRC-100-5545	■	Light Light Black	4	55%±5%	45%	99%	45%	0.56

\*Above colors are for reference only, figures are laboratory test results, actual production may vary from batch to batch

### HIGHLIGHTS

Thick and hard coating cover, the safety film is one of the kinds for defending vandalism behaviors. In case of break in / smash & grab, the glass will stay in one piece and will not fall off or scattering, which protect whatever behind the window from smashed glass. Not only preventing scattering, but also make the window to last a longer time when delay of force entry is desired, make it more difficult

### FEATURES

- Films 4 MIL can be used in automotive
- Colored Safety Films available
- Tough coating cover
- Prevent glass from scattering
- Delay force entry in case of break in / smash & grab